

Robot Programming with Lisp

3. Functional Programming: Functions, Lexical Scope and Closures

Gayane Kazhoyan

Institute for Artificial Intelligence
Universität Bremen

19th April, 2016

Outline

Background

Theory

Organizational

Background

Gayane Kazhoyan

19th April, 2016

Theory

Organizational

Robot Programming with Lisp

2

Functional Programming

Pure functional programming concepts include:

- no program *state* (e.g. no global variables);

Functional Programming

Pure functional programming concepts include:

- no program *state* (e.g. no global variables);
- *referential transparency*, i.e. a function called twice with same arguments always generates the same output;

Functional Programming

Pure functional programming concepts include:

- no program *state* (e.g. no global variables);
- *referential transparency*, i.e. a function called twice with same arguments always generates the same output;
- functions don't have *side effects*;

Functional Programming

Pure functional programming concepts include:

- no program *state* (e.g. no global variables);
- *referential transparency*, i.e. a function called twice with same arguments always generates the same output;
- functions don't have *side effects*;
- avoid mutable data, i.e. once created, data structure values don't change (*immutable data*);

Functional Programming

Pure functional programming concepts include:

- no program *state* (e.g. no global variables);
- *referential transparency*, i.e. a function called twice with same arguments always generates the same output;
- functions don't have *side effects*;
- avoid mutable data, i.e. once created, data structure values don't change (*immutable data*);
- heavy usage of *recursions*, as opposed to iterative approaches;

Functional Programming

Pure functional programming concepts include:

- no program *state* (e.g. no global variables);
- *referential transparency*, i.e. a function called twice with same arguments always generates the same output;
- functions don't have *side effects*;
- avoid mutable data, i.e. once created, data structure values don't change (*immutable data*);
- heavy usage of *recursions*, as opposed to iterative approaches;
- functions as *first class citizens*, as a result, higher-order functions (simplest analogy: callbacks);

Functional Programming

Pure functional programming concepts include:

- no program *state* (e.g. no global variables);
- *referential transparency*, i.e. a function called twice with same arguments always generates the same output;
- functions don't have *side effects*;
- avoid mutable data, i.e. once created, data structure values don't change (*immutable data*);
- heavy usage of *recursions*, as opposed to iterative approaches;
- functions as *first class citizens*, as a result, higher-order functions (simplest analogy: callbacks);
- *lazy evaluations*, i.e. only execute a function call when its result is actually used;

Functional Programming

Pure functional programming concepts include:

- no program *state* (e.g. no global variables);
- *referential transparency*, i.e. a function called twice with same arguments always generates the same output;
- functions don't have *side effects*;
- avoid mutable data, i.e. once created, data structure values don't change (*immutable data*);
- heavy usage of *recursions*, as opposed to iterative approaches;
- functions as *first class citizens*, as a result, higher-order functions (simplest analogy: callbacks);
- *lazy evaluations*, i.e. only execute a function call when its result is actually used;
- usage of lists as a main data structure;

Popular Languages

- **Scheme:** 1975, latest release in 2013, introduced many core functional programming concepts that are widely accepted today

Popular Languages

- **Scheme**: 1975, latest release in 2013, introduced many core functional programming concepts that are widely accepted today
- **Common Lisp**: 1984, latest release (SBCL) in 2016, successor of Scheme, possibly the most influential, general-purpose, widely-used Lisp dialect

Popular Languages

- **Scheme**: 1975, latest release in 2013, introduced many core functional programming concepts that are widely accepted today
- **Common Lisp**: 1984, latest release (SBCL) in 2016, successor of Scheme, possibly the most influential, general-purpose, widely-used Lisp dialect
- **Erlang**: 1986, latest release in 2016, focused on concurrency and distributed systems, supports hot patching, used within AWS

Popular Languages

- **Scheme**: 1975, latest release in 2013, introduced many core functional programming concepts that are widely accepted today
- **Common Lisp**: 1984, latest release (SBCL) in 2016, successor of Scheme, possibly the most influential, general-purpose, widely-used Lisp dialect
- **Erlang**: 1986, latest release in 2016, focused on concurrency and distributed systems, supports hot patching, used within AWS
- **Haskell**: 1990, latest release in 2010, purely functional, in contrast to all others in this list

Popular Languages

- **Scheme**: 1975, latest release in 2013, introduced many core functional programming concepts that are widely accepted today
- **Common Lisp**: 1984, latest release (SBCL) in 2016, successor of Scheme, possibly the most influential, general-purpose, widely-used Lisp dialect
- **Erlang**: 1986, latest release in 2016, focused on concurrency and distributed systems, supports hot patching, used within AWS
- **Haskell**: 1990, latest release in 2010, purely functional, in contrast to all others in this list
- **Racket**: 1994, latest release in 2016, focused on writing domain-specific programming languages

Popular Languages [2]

- **OCaml**: 1996, latest release in 2015, very high performance, static-typed, one of the first inherently object-oriented functional programming languages

Popular Languages [2]

- **OCaml**: 1996, latest release in 2015, very high performance, static-typed, one of the first inherently object-oriented functional programming languages
- **Scala**: 2003, latest release in 2016, compiled to JVM code, static-typed, object-oriented, Java-like syntax `{ }`

Popular Languages [2]

- **OCaml**: 1996, latest release in 2015, very high performance, static-typed, one of the first inherently object-oriented functional programming languages
- **Scala**: 2003, latest release in 2016, compiled to JVM code, static-typed, object-oriented, Java-like syntax `{}`
- **Clojure**: 2007, latest release in 2016, compiled to JVM code and JavaScript, therefore mostly used in Web, seems to be fashionable in the programming subculture at the moment

Popular Languages [2]

- **OCaml**: 1996, latest release in 2015, very high performance, static-typed, one of the first inherently object-oriented functional programming languages
- **Scala**: 2003, latest release in 2016, compiled to JVM code, static-typed, object-oriented, Java-like syntax `{ }`
- **Clojure**: 2007, latest release in 2016, compiled to JVM code and JavaScript, therefore mostly used in Web, seems to be fashionable in the programming subculture at the moment
- **Julia**: 2012, latest release in 2016, focused on high-performance numerical and scientific computing, means for distributed computation, strong FFI support, Python-like syntax

Popular Languages [2]

- **OCaml**: 1996, latest release in 2015, very high performance, static-typed, one of the first inherently object-oriented functional programming languages
- **Scala**: 2003, latest release in 2016, compiled to JVM code, static-typed, object-oriented, Java-like syntax `{}`
- **Clojure**: 2007, latest release in 2016, compiled to JVM code and JavaScript, therefore mostly used in Web, seems to be fashionable in the programming subculture at the moment
- **Julia**: 2012, latest release in 2016, focused on high-performance numerical and scientific computing, means for distributed computation, strong FFI support, Python-like syntax

Conclusion: functional programming becomes more and more popular.

Outline

Background

Theory

Organizational

Background

Theory

Organizational

Defining a Function

Signature

```
CL-USER>
(defun my-cool-function-name (arg-1 arg-2 arg-3 arg-4)
  "This function combines its 4 input arguments into a list
and returns it."
  (list arg-1 arg-2 arg-3 arg-4))
```

Optional Arguments

```
CL-USER> (defun optional-arguments (arg-1 arg-2 &optional arg-3 arg-4)
          (list arg-1 arg-2 arg-3 arg-4))
CL-USER> (optional-arguments 1 2 3 4)
(1 2 3 4)
CL-USER> (optional-arguments 1 2 3)
(1 2 3 NIL)
CL-USER> (optional-arguments 304)
invalid number of arguments: 1
```

Defining a Function [2]

Key Arguments

```
CL-USER>
```

```
(defun specific-optional (arg-1 arg-2 &key arg-3 arg-4)
  "This function demonstrates how to pass a value to
  a specific optional argument."
  (list arg-1 arg-2 arg-3 arg-4))
SPECIFIC-OPTIONAL
```

```
CL-USER> (specific-optional 1 2 3 4)
unknown &KEY argument: 3
```

```
CL-USER> (specific-optional 1 2 :arg-4 4)
(1 2 NIL 4)
```

Defining a Function [3]

Unlimited Number of Arguments

```
CL-USER> (defun unlimited-args (arg-1 &rest args)
           (format t "Type of args is ~a.~%" (type-of args))
           (cons (list arg-1) args))
```

```
UNLIMITED-ARGS
```

```
CL-USER> (unlimited-args 1 2 3 4)
Type of args is CONS.
(1 2 3 4)
```

```
CL-USER> (unlimited-args 1)
Type of args is NULL.
(1)
```


Multiple Values

list vs. values

```
CL-USER> (defvar *some-list* (list 1 2 3))
*SOME-LIST*
CL-USER> *some-list*
(1 2 3)
CL-USER> (defvar *values?* (values 1 2 3))
*VALUES?*
CL-USER> *values?*
1
CL-USER> (values 1 2 3)
1
2
3
CL-USER> *
1
CL-USER> //
(1 2 3)
```

Multiple Values [2]

Returning Multiple Values!

```
CL-USER> (defvar *db* '((Anna 1987) (Bob 1899) (Charlie 1980)))
           (defun name-and-birth-year (id)
             (values (first (nth (- id 1) *db*))
                     (second (nth (- id 1) *db*)))))
```

NAME-AND-BIRTH-YEAR

```
CL-USER> (name-and-birth-year 2)
BOB
1899
```

```
CL-USER> (multiple-value-bind (name year) (name-and-birth-year 2)
           (format t "~a was born in ~a.~%" name year))
BOB was born in 1899.
NIL
```

Function Designators

Similar to C pointers or Java references

Designator of a Function

```
CL-USER> (describe '+)
COMMON-LISP:+
 [symbol]
+ names a special variable:
+ names a compiled function:
CL-USER> #' +
CL-USER> (symbol-function '+)
#<FUNCTION +>
CL-USER> (describe #' +)
#<FUNCTION +>
 [compiled function]
Lambda-list: (&REST NUMBERS)
Declared type: (FUNCTION (&REST NUMBER) (VALUES NUMBER &OPTIONAL))
Derived type: (FUNCTION (&REST T) (VALUES NUMBER &OPTIONAL))
Documentation: ...
Source file: SYS:SRC;CODE;NUMBERS.LISP
```

Background

Theory

Organizational

Higher-order Functions

Function as Argument

```
CL-USER> (funcall #' + 1 2 3)
CL-USER> (apply #' + '(1 2 3))
6
CL-USER> (defun transform-1 (num) (/ 1.0 num))
TRANSFORM-1
CL-USER> (defun transform-2 (num) (sqrt num))
TRANSFORM-2
CL-USER> (defun print-transformed (a-number a-function)
           (format t "~a transformed with ~a becomes ~a.~%"
                   a-number a-function (funcall a-function a-number)))
PRINT-TRANSFORMED
CL-USER> (print-transformed 4 #'transform-1)
4 transformed with #<FUNCTION TRANSFORM-1> becomes 0.25.
CL-USER> (print-transformed 4 #'transform-2)
4 transformed with #<FUNCTION TRANSFORM-2> becomes 2.0.
CL-USER> (sort '(2 6 3 7 1 5) #'>)
(7 6 5 3 2 1)
```

Higher-order Functions [2]

Function as Return Value

```
CL-USER> (defun give-me-some-function ()  
           (case (random 5)  
             (0 #'+)  
             (1 #'-)  
             (2 #'*)  
             (3 #'/  
             (4 #'values)))
```

```
GIVE-ME-SOME-FUNCTION
```

```
CL-USER> (give-me-some-function)  
#<FUNCTION ->
```

```
CL-USER> (funcall (give-me-some-function) 10 5)  
5
```

```
CL-USER> (funcall (give-me-some-function) 10 5)  
2
```

Anonymous Functions

lambda

```
CL-USER> (sort '((1 2 3 4) (3 4) (6 3 6)) #'>)
The value (3 4) is not of type NUMBER.
CL-USER> (sort '((1 2 3 4) (3 4) (6 3 6))
             (lambda (x y)
               (> (length x) (length y))))
((1 2 3 4) (6 3 6) (3 4))
CL-USER> (sort '((1 2 3 4) (3 4) (6 3 6)) #'> :key #'car)
((6 3 6) (3 4) (1 2 3 4))

CL-USER> (defun random-generator-a-to-b (a b)
           (lambda () (+ (random (- b a)) a)))
RANDOM-GENERATOR-A-TO-B
CL-USER> (random-generator-a-to-b 5 10)
#<CLOSURE (LAMBDA () :IN RANDOM-GENERATOR-A-TO-B) {100D31F90B}>
CL-USER> (funcall (random-generator-a-to-b 5 10))
9
```

The let Environment

```
let
```

```
CL-USER> (let ((a 1)
                (b 2))
           (values a b))
```

```
1
2
```

```
CL-USER> (values a b)
The variable A is unbound.
```

```
CL-USER> (defvar some-var 'global)
(let ((some-var 'outer))
  (let ((some-var 'inter))
    (format t "some-var inner: ~a~%" some-var)
    (format t "some-var outer: ~a~%" some-var)
    (format t "global-var: ~a~%" some-var)
```

```
?
```

The let Environment

```
let
```

```
CL-USER> (let ((a 1)
                (b 2))
           (values a b))
```

```
1
2
```

```
CL-USER> (values a b)
The variable A is unbound.
```

```
CL-USER> (defvar some-var 'global)
(let ((some-var 'outer))
  (let ((some-var 'inter))
    (format t "some-var inner: ~a~%" some-var)
    (format t "some-var outer: ~a~%" some-var)
    (format t "global-var: ~a~%" some-var)
```

```
some-var inner: INTER
some-var outer: OUTER
global-var: GLOBAL
```


The let Environment [2]

```
let*
```

```
CL-USER> (let ((a 4)
               (a^2 (expt a 2)))
           (values a a^2))
```

The variable A is unbound.

```
CL-USER> (let* ((a 4)
                (a^2 (expt a 2)))
           (values a a^2))
```

```
4
16
```

Lexical Scope

In Lisp, non-global **variable values** are, when possible, **determined at compile time**. They are **bound lexically**, i.e. they are bound to the code they're defined in, not to the run-time state of the program.

Riddle

```
CL-USER> (let* ((lexical-var 304)
                (some-lambda (lambda () (+ lexical-var 100))))
           (setf lexical-var 4)
           (funcall some-lambda))
?
```

Lexical Scope

In Lisp, non-global **variable values are**, when possible, **determined at compile time**. They are **bound lexically**, i.e. they are bound to the code they're defined in, not to the run-time state of the program.

Riddle

```
CL-USER> (let* ((lexical-var 304)
                (some-lambda (lambda () (+ lexical-var 100))))
           (setf lexical-var 4)
           (funcall some-lambda))
```

104

This is one single `let` block, therefore `lexical-var` is the same everywhere in the block.

Lexical Scope [2]

Lexical scope with `lambda` and `defun`

```
CL-USER> (defun return-x (x)
           (let ((x 304))
             x))
           (return-x 3)
```

?

Lexical Scope [2]

Lexical scope with `lambda` and `defun`

```
CL-USER> (defun return-x (x)
           (let ((x 304))
             x))
           (return-x 3)
```

304

`lambda`-s and `defun`-s create lexical local variables per default.

Lexical Scope [3]

More Examples

```
CL-USER> (let* ((lexical-var 304)
                (some-lambda (lambda () (+ lexical-var 100))))
           (setf lexical-var 4)
           (funcall some-lambda))
104
CL-USER> lexical-var
?
```

Lexical Scope [3]

More Examples

```
CL-USER> (let* ((lexical-var 304)
                (some-lambda (lambda () (+ lexical-var 100))))
           (setf lexical-var 4)
           (funcall some-lambda))
```

104

```
CL-USER> lexical-var
; Evaluation aborted on #<UNBOUND-VARIABLE LEXICAL-VAR {100AA9C403}>.
```

```
CL-USER> (let ((another-var 304)
                (another-lambda (lambda () (+ another-var 100))))
           (setf another-var 4)
           (funcall another-lambda))
```

?

Lexical Scope [3]

More Examples

```
CL-USER> (let* ((lexical-var 304)
                (some-lambda (lambda () (+ lexical-var 100))))
           (setf lexical-var 4)
           (funcall some-lambda))
104
CL-USER> lexical-var
; Evaluation aborted on #<UNBOUND-VARIABLE LEXICAL-VAR {100AA9C403}>.
```

```
CL-USER> (let ((another-var 304)
                (another-lambda (lambda () (+ another-var 100))))
           (setf another-var 4)
           (funcall another-lambda))
; caught WARNING:
;   undefined variable: ANOTHER-VAR
; Evaluation aborted on #<UNBOUND-VARIABLE ANOTHER-VAR {100AD51473}>.
```


Lexical Scope [3]

More Examples

```
CL-USER> (let ((other-lambda (lambda () (+ other-var 100))))  
          (setf other-var 4)  
          (funcall other-lambda))  
?
```

Lexical Scope [3]

More Examples

```
CL-USER> (let ((other-lambda (lambda () (+ other-var 100))))
           (setf other-var 4)
           (funcall other-lambda))
; caught WARNING:
;   undefined variable: OTHER-VAR
104
CL-USER> other-var
4
CL-USER> (describe 'other-var)
COMMON-LISP-USER::OTHER-VAR
 [symbol]
OTHER-VAR names an undefined variable:
  Value: 4
```

Lexical Scope [3]

More Examples

```
CL-USER> (let ((some-var 304))  
           (defun some-fun () (+ some-var 100))  
           (setf some-var 4)  
           (funcall #'some-fun))
```

?

Lexical Scope [3]

More Examples

```
CL-USER> (let ((some-var 304))
           (defun some-fun () (+ some-var 100))
           (setf some-var 4)
           (funcall #'some-fun))
```

104

```
;; Alt-. on DEFUN brings you to "defboot.lisp"
(defmacro mundanely defun (&environment env name args &body body)
  (multiple-value-bind (forms decls doc) (parse-body body)
    (let* ((lambda-guts `(,args ...))
           (lambda `(lambda ,@lambda-guts)) ...)
      ...
```

Lexical Scope [3]

Riddle #2

```
CL-USER> (defvar y 'global)
CL-USER> (defun return-global-y ()
           y)
           (return-global-y)

GLOBAL
CL-USER> (defun return-local-y (y)
           y)
           (return-local-y 'argument)

ARGUMENT
CL-USER> (defun return-?-y (y)
           (return-global-y))
           (return-?-y 'argument-again)

?
```

Lexical Scope [3]

Riddle #2

```
CL-USER> (defvar y 'global)
CL-USER> (defun return-global-y ()
           y)
           (return-global-y)
GLOBAL
CL-USER> (defun return-local-y (y)
           y)
           (return-local-y 'argument)
ARGUMENT
CL-USER> (defun return-?-y (y)
           (return-global-y))
           (return-?-y 'argument-again)
ARGUMENT-AGAIN
```

`defvar` and `defparameter` create dynamically-bound variables.

Closures

Counter

```
CL-USER> (defun increment-counter ()
           (let ((counter 0))
             (incf counter)))
(increment-counter)
(increment-counter)

1
CL-USER> (defun increment-counter-closure ()
           (let ((counter 0))
             (lambda () (incf counter))))
INCREMENT-COUNTER-CLOSURE
CL-USER> (let ((function-object (increment-counter-closure)))
           (format t "counting: ~a ~a~%"
                   (funcall function-object) (funcall function-object)))
counting: 1 2
```

Closure is a function that, in addition to its specific functionality, also encloses its lexical environment (environment as in, e.g., terminal environment variables).

Closures [2]

Counter Again

```
CL-USER> (defun increment-counter-lambda ()
           (let ((counter 0))
               (lambda (counter) (incf counter))))
INCREMENT-COUNTER-LAMBDA
CL-USER> (let ((function-object (increment-counter-lambda)))
           (format t "counter: ~a~%" (funcall function-object 0))
           (format t "once more: ~a~%" (funcall function-object 0)))
counter: 1
once more: 1
CL-USER> (let ((function-object (increment-counter-closure)))
           (format t "counter: ~a~%" (funcall function-object))
           (setf counter 0)
           (format t "counter: ~a~%" (funcall function-object)))
counter: 1
counter: 2
```

Encapsulation!

Background

Theory

Organizational

Currying

Back to Generators

```
CL-USER> (let ((x^10-lambda (lambda (x) (expt x 10))))
          (dolist (elem '(2 3))
            (format t "~a^10 = ~a~%" elem (funcall x^10-lambda elem))))
2^10 = 1024
3^10 = 59049
;; The following only works with roslisp_repl. Otherwise do first:
;; (pushnew #p"/.../alexandria" asdf:*central-registry* :test #'equal)
CL-USER> (asdf:load-system :alexandria)
CL-USER> (dolist (elem '(2 3))
          (format t "~a^10 = ~a~%"
                  elem (funcall (alexandria:curry #'expt 10) elem)))
2^10 = 100
3^10 = 1000
CL-USER> (dolist (elem '(2 3))
          (format t "~a^10 = ~a~%"
                  elem (funcall (alexandria:rcurry #'expt 10) elem)))
2^10 = 1024
3^10 = 59049
```

Guidelines

- Don't use global variables! Only for constants.
- If your function generates side-effects, name it correspondingly (either `foo!` which is preferred, or `foof` as in `setf`, or `nfoo` as in `nconc`)
- Use `Ctrl-Alt-\` on a selected region to fix indentation
- Try to keep the brackets all together:

This looks weird in Lisp

```
(if condition
  do-this
  do-that
)
```

Links

- Alexandria documentation:

<http://common-lisp.net/project/alexandria/draft/alexandria.html>

Outline

Background

Theory

Organizational

Background

Theory

Organizational

Info Summary

- Assignment code: REPO/assignment_3/src/...
- Assignment points: 10 out of 50
- Assignment due: 26.04, Tuesday, 08:00 AM German time
- Next class: 26.04, 16:15

Q & A

Thanks for your attention!